

AU - 2009 Rapid Sheet Dryer



This instrument is used for shortening the drying time of wet pulp or paper samples before determining the dry weight or moisture content. It is provided with flat heating elements. Stainless steel sheet fabrications with insulating material ensure long service life.

Suitable for Sheet Size:

Max. width 250 mm, Max length 300 mm.

Temperature adjustable over a wide range upto maximum of 180° ± 10°C.

SPECIFICATIONS

Rectangular Drying Plates.
 Lower plate is lined with wire cloth to lead off the vapour during the drying process.
 Provided with overheating protector.
 Switch provided with indicator lamp.
 Upper and lower drying plates are heated with flat electrical elements.

Sheet Size	: Max. width 250 mm Max length 300 mm
Temperature range	: Adjustable over a wide range, upto maximum of 180 °C ± 10 °C.
Heaters	: Flat Electrical Elements single phase, 220 V, 400 W each for upper and lower plates
Power Supply / Consumption	: 220 V, Single Phase, 50 Hz. / 800 W
Applicable Standard	: SCAN M- 1

	Shipping Data	Ordering Data
	Net Weight	Model No.
	Gross weight	Voltage
	Dimension	Frequency

Changes:

UEC products undergo continuous development. The technical data in this catalogue are therefore subject to change