

Test voltages in complete safety!

Testers



- **C.A 730:** 230 V phase test, without contact
- **C.A 735 / 745:** no risk of triggering high-sensitivity RCD's during a phase/earth test
- **C.A 745:** continuity and resistance test, phase test with a single test probe
- As per IEC 61010-1 safety standards

Professional specifications in conformity with safety standards



C.A 745



C.A 735



C.A 730

Voltage test	12 V to 690 V AC/DC (7 diodes)	
	audible beep U > 50 V AC	-
Impedance	400 kΩ	
Identification of phase/neutral	"Ph" diode flashing and intermittent beep for U > 100 V AC	-
Working frequency	DC and 50/60 Hz	
Polarity test	"+" and "-" diodes	
Voltage protection	up to 1,000 V for 30 seconds	
Audible continuity	R < 2 kΩ	
Resistance test	2 kΩ to 300 kΩ (3 diodes)	
Protection on resistance	up to 550 V	

Phase detection without contact 195 V AC < U < 265 V AC
45 Hz to 400 Hz

POWER SUPPLY

- 9 V standard battery (type 6 F 22 or 6 LF 22)
- Battery life with alkaline battery (6 LF 22):
 - C.A 730: 35,000 tests of 5 seconds
 - C.A 735: 10,000 tests of 5 seconds
 - C.A 745: 3,500 tests of 5 seconds

DIMENSIONS AND WEIGHT

- C.A 730
 - 179 x 47 x 33 mm - 120 g
- C.A 735/745
 - 193 x 47 X 36 mm - 170 g
 - Fitted lead: 1.20 m
 - Test probe Ø 2 and 3.7 mm



Your tester is always handy with its case, supplied as an accessory.

References to order	
C.A 730	P01101738Z
C.A 735	P01101734
C.A 745	P01101736Z
Accessories	
Carrying case	P01298012
Carrying case	P01298012Z
Spare for C.A 745	
Red test probe for CAT III/CAT IV.....	P01295457Z

Reminder of markings used in conformity with IEC 61010-1

~: AC ≈: DC or AC

600 V CAT III ⚡: max voltage 600 V in relation to the earth for installation category III

⚠: refer to the user's manual

ENVIRONMENTAL CONDITIONS

- Temperature: -10 °C to +55 °C
- Relative humidity: 10 to 90 % RH

CONFORMITY WITH STANDARDS

- Electrical safety (IEC 61010-1):
 - Double insulation ☐
 - Installation category III
 - Degree of pollution 2
 - Voltage 600 V
- Electromagnetic compatibility: CE marking (EN 50081-1/50082-1)

YOUR DISTRIBUTOR

