

• TM-100: Sound Level Calibrator

Features:

- Setting standard sound level at 94dB and 114dB
- According Standard: ANSI S1.4-1984 and IEC 942 1988 Class 2
- Low battery indicator



Specifications:

Model:	TM-100	
Size	48(Ø) x125(H) mm	
Weight	0.29kg	
Output Frequency	Test Condition	Accuracy
1KHz ±4%	a. Environment Temp: 20°C b. Relative humidity: 65% c. Atmospheric pressure: 1013 mbar	±0.5dB

• TM-101: Professional Digital Sound Level Meter

Features:

- Fast/Slow sampling - with hold feature
- Analogue AC/DC output
- Alarm feature
- DC power input (PSU not supplied)
- Approved to IEC-651 Type2 and ANSI S1.4 Type2
- 1/4" UNC tripod mount fitting
- Supplied in carry case
- Supplied with batteries



Specifications:

Model:	TM-101
Test ranges	30 ~ 130dB, LO: 30~80dB, MED: 50 ~ 100dB, HI: 80 ~ 130dB
Accuracy	±1.5dB (ref 94dB @ 1kHz)
Resolution	0.1dB
Microphone	1/2 " Electret condenser microphone
Frequency Weighting	AC
Time Weighting	Fast/Slow
Dynamic Range	50dB
Frequency Range	31.5Hz ~ 8kHz
Size	80(W) x 280(H) x 32(D) mm
Weight (including battery)	0.3kg